

1





2

3

4

5

SIGN	DESCRIPTION	DATE	APPROVER



N=Number of contacts

Technical Data:

Material:

Contact(metal housing): Copper Alloy, Ni plated.

Terminal screw: Steel galvanized with Cr3+ plated

Wire guard: Copper Alloy, Tin plated.

Insulator body(housing): Polyamide(UL94V-0)

Electrical

Voltage rating: 300VAC

Current rating: 12 Amps/way max

Contact resistance: 20mΩ (max)

Withstanding Voltage: 2500VAC(1min) Test time=60sec/1pcs

Wire range: 16-24AWG

Mechanical:

Torque: 2.5kgf.cm/M2

Operating temperature: -40°C to +105°C

Soldering reliability:

Test temperature= 250°C±10°C

5 seconds max

Ordering Information:

F73-C-C XX-X 0 0 X 0

2 02 5 Green
4 04 6 Blue
20 20 A Black
1 "-"Screw
2 "-/+ "Screw

WELINK 上海拓尔普电子科技有限公司
Welink International Co., LTD.

TOLERANCE	APPROVED:	NAME:
X. ±0.50	CHECKED:	F73-C Pitch 3.81mm
X.X ±0.30	DRAWN: Yang Ming 2012.06.20	Series
X.XX ±0.20	UNITS: mm	PART NO: F73CCXX100X0
X° ±1°	REV: A	DWG NO: 9F73CC001A
	SCALE: 4 / 1	PAGE: 1 / 1